

JT-CELL500

- Low profile designed to fit 48mm (1 7/8") to 51mm (2") truss tubes
- Ideal for exhibitions, displays & light duty applications
- Precision extruded high tensile aluminium alloy
- Compatible with JT30/JT30H/JT40H/GP30/GP52/ST30/ST52/ST76R/LP60 truss series
- CE certified
- Rated with Safety Factor 8:1 DGUV17/BGVC1 (SWL)
- Mounting hole for up to 13mm (1/2") bolts
- Polished surface with micro-percussion markings
- Powder coated versions available on request



JT-CELL501

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
230 (507)		0.14 (0.30)		48-51 (1 7/8"-2")	


Basic truss clamp



JT-CELL502

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
230 (507)		0.22 (0.47)		48-51 (1 7/8"-2")	

Quick truss clamp with bolt + wingnut




JT-CELL504

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
230 (507)		0.27 (0.60)		48-51 (1 7/8"-2")	

Swivel truss coupler

JT-CELL600

- Hook clamp series designed to fit 48mm (1 7/8") to 51mm (2") truss tubes
- Quick & easy attachment solution for moving heads and heavy fixtures
- Precision extruded high tensile aluminium alloy
- Compatible with JT30/JT30H/JT40H/GP30/GP52/ST30/ST52/ST76R/LP60 truss series
- CE certified
- Rated with Safety Factor 8:1 DGUV17/BGVC1 (SWL)
- Mounting hole for up to 13mm (1/2") bolts
- Polished surface with micro-percussion markings
- Powder coated versions available on request



JT-CELL601

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
350 (771)		0.50 (1.10)		48-51 (1 7/8"-2")	


Basic truss clamp



JT-CELL602

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
350 (771)		0.58 (1.28)		48-51 (1 7/8"-2")	

Truss clamp with bolt + large wingnut



JT-CELL603

kg	lbs	kg	lbs	mm	in
SWL		Weight		Tube	
350 (771)		0.75 (1.65)		48-51 (1 7/8"-2")	

Truss clamp with lifting eye

